

STOBITEX Wear Protection Sleeve PU-1/single

Product information



Special wear protection for roundslings and webbing slings, intended for lift of load with cutting edges. Extremely good cutting resistance and high wear strength.

Also available as double sided sheathes, STOBITEX Wear Protection Sleeve PU-2/double side.

Material: Polyurethane.

Temperature range: Approx. -30° up to +70°C, short expose to approx. +90°C.

Part Code	Size	For 2 layer lifting mm	For 4 layer lifting mm	For roundslings ton	a mm	i mm	h mm	w mm	A mm	Weight kg/m
12.4000200020	50	30	-	-	50	40	10	5	-	0.85
12.4000200030	50	-	30	-	50	40	20	5	-	0.9
12.4000200060	70	50	-	-	70	60	12	5	-	1.25
12.4000200061	70	-	50	-	70	60	17	5	-	1.3
12.4000200070	80	60	-	-	80	70	12	5	-	1.3
12.4000200090	80	-	60	-	-	70	24	-	80	1.35
12.4000200095	85	-	-	1	85	75	12	5	-	1.35
12.4000200110	95	-	-	2	95	85	24	5	-	1.5

12.4000200120	110	90	-	-	110	100	12	5	-	1.55
12.4000200130	110	-	-	3	110	100	174	5	-	1.6
12.4000200140	110	-	90	-	110	100	24	5	-	1.6
12.4000200190	145	120	-	-	145	135	12	5	-	2
12.4000200200	145	-	120	-	145	135	24	5	-	2.1
12.4000200240	170	150	-	-	170	160	12	5	-	2.3
12.4000200250	170	-	-	6	170	160	17	5	-	2.4
12.4000200260	170	-	150	-	170	160	24	5	-	2.4
12.4000200280	200	180	-	-	200	190	12	5	-	2.6
12.4000200290	200	-	-	8	200	190	17	5	-	2.65
12.4000200300	200	-	180	-	200	190	24	5	-	2.7
12.4000200320	230	-	-	10	230	220	36	5	-	3.5
12.4000200340	260	240	-	-	260	250	15	8	-	3.9
12.4000200360	290	-	-	15	290	280	30	8	-	4.4
12.4000200370	330	300	-	-	330	320	15	8	-	4.4
12.4000200380	330	-	300	-	330	320	30	8	-	4.8
12.4000200390	330	-	-	20	330	320	45	8	-	5.3

Blueprint

