



Master Link Assembly Pewag VSW 2-4

Product information

This master link assembly is designed for the effortless creation of II- and IV-leg chain slings in the assembled or welded system. The flattened section on the transition links opens up additional, universal connection possibilities. Extra-large rings make this master link assembly the perfect partner for crane hooks according to DIN 15401 up to no. 40 and according to DIN 15402 up to no. 50.

Material: High-alloy quenched and tempered steel

Marking: According to standard, CE-marked, brand, grade

Temperature range: -40° up to +380°

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Part Code	Code	WLL ton	Chain 2 legs	Chain 3 and 4 legs	Single hook DIN 15401 no.	Double hook DIN 15402 no.	d mm	e mm	s mm	t mm	w mm	Weight kg
11.029314	VSW 2-10 / 4-8	5.6	10	8	40	50	30	515	24	430	220	8.16
11.029315	VSW 2-13 / 4-10	9.5	13	10	40	50	33	515	26	430	220	9.66
11.029317	VSW 2-16 / 4-13	14	16	13	40	50	36	545	29	430	220	12.32
11.029319	VSW 2-19/20 / 4-16	21.2	19/20	16	40	50	45	570	-	430	220	19.54

Blueprint

