



Eye Nut EL, Green Pin®

Product information

The Green Pin® Eye Nut is a grade 8 eye nut. These eye nuts have a flat on the eye, which enables the assembly with an omega link or a thimble. They have ISO metric threads as standard, however UNC threads are also available. The Green Pin® Eye Nut is available in a range with a working load limit from 0.2 t. up to 18 t.

Certification: at no extra charge this product can be supplied with a works certificate, a 3.1 material certificate and/or EC Declaration of Conformity

Material: alloy steel, quenched and tempered

Marking: CE-marked

Temperature range: -40°C up to +200°C

Finish: Painted red or white

Safety factor: 5:1

Grade: 8

Part Code	Diameter mm	WLL ton	Thread mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	Weight kg
11.40EL6R	11	0.2	M6 x 1.00	6	31	51	30	14	44	6	6	0.15
11.40EL8R	11	0.4	M8 x 1.25	8	31	51	30	14	44	11	6	0.15
11.40EL10R	11	0.7	M10 x 1.50	10	31	51	30	14	44	11	6	0.15
11.40EL12R	12	1	M12 x 1.75	12	39	56	32	15	48	12	6	0.23
11.40EL14R	12	1.2	M14 x 2.00	14	39	56	32	15	48	12	6	0.23
11.40EL16R	14	1.5	M16 x 2.00	16	44	65	37	16	60	14	8	0.4
11.40EL18R	14	2	M18 x 2.50	18	44	65	37	16	60	14	8	0.4
11.40EL20R	14	2.5	M20 x 2.50	20	44	65	37	16	60	14	8	0.4
11.40EL22R	16	3	M22 x 2.50	22	52	80	48	21	75	16	11	0.63
11.40EL24R	16	4	M24 x 3.00	24	52	80	48	21	75	16	11	0.63
11.40EL27R	16	5	M27 x 3.00	27	52	80	48	21	75	16	11	0.63
11.40EL30R	21	6	M30 x 3.50	30	66	96	58	25	88	21	14	1.11
11.40EL33R	21	7	M33 x 3.50	33	66	96	58	25	88	21	14	1.11
11.40EL36R	25	8	M36 x 4.00	36	84	121	73	39	100	25	17	2.22
11.40EL39R	25	9	M39 x 4.00	39	84	121	73	39	100	25	17	2.22
11.40EL42R	25	10	M42 x 4.50	42	84	121	73	39	100	25	17	2.22
11.40EL45R	25	15	M45 x 4.50	45	90	132	82	42	121	25	22	2.73
11.40EL48R	25	18	M48 x 5.00	48	90	132	82	42	121	25	22	2.73

Technical data

Blueprint

