



## Sunken Hole Shackle G-4159

### Product information

Dee shackles with square sunken hole screw pin.

**Certification:** This product can be supplied with a works certificate, 3.1 certificate, manufacturer test certificate and/or EC Declaration of Conformity.

**Standard:** EN 13889 and meets performance requirements of US Fed. Spec. RR-C271, Grade A.

**Material:** Bow and pin high tensile steel, quenched and tempered

**Marking:** According to standard, CE-marked

**Finish:** Hot dipped galvanized

**Standard:** EN 13889

**Note:** Key for (un)screwing the pin sold separately

**Safety factor:** 6:1

**Grade:** 6

Part Code	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	i mm	Weight kg
11.30PGDVV13	2	13.5	16	34	13	22	43	81	51	11	0.34
11.30PGDVV16	3.25	16	19	40	16	27	51	97	63	11	0.6
11.30PGDVV19	4.75	19	22	46	19	31	59	112	74	11	0.98
11.30PGDVV22	6.5	22	25	52	22	36	73	134	85	13	1.26
11.30PGDVV25	8.5	25	28	59	25	43	85	154	99	13	2.14
11.30PGDVV28	9.5	28	32	66	28	47	90	167	110	17	3.05
11.30PGDVV32	12	32	35	72	32	51	94	180	122	17	3.56
11.30PGDVV38	17	38	42	88	38	60	127	230	145	17	6.84

## Blueprint

