



Bow Shackles with Screw Collar Pin G-4161

Product information

Bow shackles with screw pin

Certification: This product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles starting from 2 t can be supplied with DNV 2.7-1 certificate.

Standard: EN 13889 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVA Class 2, Grade A.

Material: Bow and pin high tensile steel, quenched and tempered

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C

Finish: Hot dip galvanized

Standard: EN 13889

Safety factor: 6:1

Grade: 6

Part Code	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	i mm	j mm	Weight kg
11.31GPGHBB05	0.33	5	6	12	5	9,5	22	16	36	29,5	26	0.02
11.31GPGHBB06	0.5	7	8	16,5	7	12	29	20	48,5	38	34	0.05
11.31GPGHBB08	0.75	9	10	20	9	13,5	32	22	56	46,5	40	0.1
11.31GPGHBB10	1	10	11	22,5	10	17	36,5	26	63,5	54	46	0.14
11.31GPGHBB11	1.5	11	13	26,5	11	19	43	29	74	59,5	51	0.19
11.31GPGHBB13	2	13,5	16	34	13	22	51	32	89	73	58	0.36
11.31GPGHBB16	3.25	16	19	40	16	27	64	43	110	89	75	0.63
11.31GPGHBB19	4.75	19	22	46	19	31	76	51	129	103	89	1.01
11.31GPGHBB22	6.5	22	25	52	22	36	83	58	144	119	102	1.5
11.31GPGHBB25	8.5	25	28	59	25	43	95	68	164	137	118	2.21
11.31GPGHBB28	9.5	28	32	66	28	47	108	75	185	153	131	3.16
11.31GPGHBB32	12	32	35	72	32	51	115	83	201	170	147	4.31
11.31GPGHBB35	13.5	35	38	80	35	57	133	92	227	186	162	5.55
11.31GPGHBB38	17	38	42	88	38	60	146	99	249	203	175	7.43
11.31GPGHBB45	25	45	50	103	45	74	178	126	300	243	216	12.84
11.31GPGHBB50	35	50	57	111	50	83	197	138	331	272	238	18.15
11.31GPGHBB57	42.5	57	65	130	57	95	222	160	377	310	274	26.29
11.31GPGHBB65	55	65	70	145	65	105	260	180	433	344	310	37.6

Blueprint

