



## Dee Shackles with Safety Bolt G-4153

### Product information

Dee shackle with safety bolt.

**Certification:** This product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles starting from 2 t can be supplied with DNV 2.7-1 certificate.

**Note:** This shackle can also be delivered with fixed nut (an extra AISI 316 securing bolt is drilled through both the nut and shackle pin. This securing bolt is fastened with two sets of Nord-Lock® washers and a securing nut. These washers lock when subjected to movement and keep the nut safely in position).

**Material:** Bow and pin high tensile steel, quenched and tempered

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C

**Finish:** Hot dip galvanized

**Standard:** EN 13889

**Safety factor:** 6:1

**Grade:** 6

Part code	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	i mm	Weight kg
11.30GPGDMB13	2	13,5	16	34	13	22	43	81	82	13	0.39
11.30GPGDMB16	3.25	16	19	40	16	27	51	97	98	17	0.67
11.30GPGDMB19	4.75	19	22	46	19	31	59	112	114	19	1.08
11.30GPGDMB22	6.5	22	25	52	22	36	73	134	130	22	1.66
11.30GPGDMB25	8.5	25	28	59	25	43	85	154	150	25	2.46
11.30GPGDMB28	9.5	28	32	66	28	47	90	167	166	27	3.4
11.30GPGDMB32	12	32	35	72	32	51	94	180	178	30	4.51
11.30GPGDMB35	13.5	35	38	80	35	57	115	209	197	33	6.1
11.30GPGDMB38	17	38	42	88	38	60	127	230	202	19	7.63
11.30GPGDMB45	25	45	50	103	45	74	149	271	249	23	12.88
11.30GPGDMB50	35	50	57	111	50	83	171	305	269	26	17.35
11.30GPGDMB57	42.5	57	65	130	57	95	190	345	301	29	25.94
11.30GPGDMB65	55	65	70	145	65	105	203	376	330	32	35.33
11.30GPGDMB75	85	75	83	162	73	127	229	427	380	39	52.97

# Blueprint

