



## Dee Shackles with Screw Collar Pin G-4151

### Product information

Dee shackle with screw collar pin.

**Certification:** This product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles starting from 2 t can be supplied with DNV 2.7-1 certificate.

**Standard:** EN 13889 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVB Class 2, Grade A.

**Material:** Bow and pin high tensile steel, quenched and tempered

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C

**Finish:** Hot dip galvanized

**Standard:** EN 13889

**Safety factor:** 6:1

**Grade:** 6

Part Code	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	Weight kg
11.30GPGDBB05	0.33	5	6	12	5	9,5	19	33	29,5	0.02
11.30GPGDBB06	0.5	7	8	16,5	7	12	22	41,5	38	0.05
11.30GPGDBB08	0.75	9	10	20	9	13,5	26	50	46,5	0.09
11.30GPGDBB10	1	10	11	22,5	10	17	32	59	54	0.14
11.30GPGDBB11	1.5	11	13	26,5	11	19	37	68	59,5	0.19
11.30GPGDBB13	2	13,5	16	34	13	22	43	81	73	0.32
11.30GPGDBB16	3.25	16	19	40	16	27	51	97	89	0.54
11.30GPGDBB19	4.75	19	22	46	19	31	59	112	103	0.87
11.30GPGDBB22	6.5	22	25	52	22	36	73	134	119	1.34
11.30GPGDBB25	8.5	25	28	59	25	43	85	154	137	2.08
11.30GPGDBB28	9.5	28	32	66	28	47	90	167	153	2.77
11.30GPGDBB32	12	32	35	72	32	51	94	180	170	3.72
11.30GPGDBB35	13.5	35	38	80	35	57	115	209	186	5.14
11.30GPGDBB38	17	38	42	88	38	60	127	230	203	6.85
11.30GPGDBB45	25	45	50	103	45	74	149	271	243	11.45
11.30GPGDBB50	35	50	57	111	50	83	171	305	272	16.86
11.30GPGDBB57	42.5	57	65	130	57	95	190	345	310	24.61
11.30GPGDBB65	55	65	70	145	65	105	203	376	344	32.65

# Blueprint

