



## Turnbuckle Hook - Hook G-6312, Green Pin®

### Product information

Turnbuckles are used for rigging or tensioning wires, ropes, rods etc. They are designed for in-line rigging, tensioning or lashing.

**Standard:** Generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b.

**Certification:** A works certificate, proof load test certificate and/or EC Declaration of Conformity can be supplied upon request.

**Material:** Drop forged high tensile steel SAE 1035 or 1045.

**Marking:** CE-marked

**Temperature range:** -20°C up to +200°C

**Finish:** Hot dip galvanized.

**Safety factor:** 5:1

Part Code	WLL ton	Thread	Take up inch	a"	b mm	c mm	d mm	e mm	f mm	g mm	Weight kg
11.51SSGPHH1006	0.54	3/8	6	3/8	278	415	13	16	15	42	0.53
11.51SSGPHH1212	0.68	1/2	12	1/2	456	739	13	19	16	47	1.34
11.51SSGPHH1206	1	1/2	6	1/2	305	434	16	22	16	48	0.93
11.51SSGPHH1209	1	1/2	9	1/2	380	587	16	22	16	47	1.16
11.51SSGPHH1909	1.36	3/4	9	3/4	468	664	20	27	24	78	2.49
11.51SSGPHH1606	1.59	5/8	6	5/8	356	479	16	23	21	67	1.4
11.51SSGPHH1612	1.59	5/8	12	5/8	507	784	16	23	21	66	1.79
11.51SSGPHH1609	1.59	5/8	9	5/8	431	632	20	24	21	66	1.96
11.51SSGPHH2518	2.27	1	18	1	778	1,191	26	35	31	106	6.5
11.51SSGPHH2524	2.27	1	24	1	928	1,495	26	35	31	105	8.13
11.51SSGPHH1906	2.36	3/4	6	3/4	393	511	22	27	24	78	2.04
11.51SSGPHH1912	2.36	3/4	12	3/4	544	816	22	27	24	78	3.27
11.51SSGPHH2506	4.54	1	6	1	479	586	26	35	31	109	4.23
11.51SSGPHH2512	4.54	1	12	1	625	886	26	35	31	106	6.64

# Blueprint

