



Turnbuckle Hook - Hook G-6312, Green Pin®

Product information

Turnbuckles are used for rigging or tensioning wires, ropes, rods etc. They are designed for in-line rigging, tensioning or lashing.

Standard: Generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b.

Certification: A works certificate, proof load test certificate and/or EC Declaration of Conformity can be supplied upon request.

Material: Drop forged high tensile steel SAE 1035 or 1045.

Marking: CE-marked

Temperature range: -20°C up to +200°C

Finish: Hot dip galvanized.

Safety factor: 5:1

| Part Code | WLL ton | Thread | Take up inch | a" | b mm | c mm | d mm | e mm | f mm | g mm | Weight kg |
|-----------------|---------|--------|--------------|-----|------|-------|------|------|------|------|-----------|
| 11.51SSGPHH1006 | 0.54 | 3/8 | 6 | 3/8 | 278 | 415 | 13 | 16 | 15 | 42 | 0.53 |
| 11.51SSGPHH1212 | 0.68 | 1/2 | 12 | 1/2 | 456 | 739 | 13 | 19 | 16 | 47 | 1.34 |
| 11.51SSGPHH1206 | 1 | 1/2 | 6 | 1/2 | 305 | 434 | 16 | 22 | 16 | 48 | 0.93 |
| 11.51SSGPHH1209 | 1 | 1/2 | 9 | 1/2 | 380 | 587 | 16 | 22 | 16 | 47 | 1.16 |
| 11.51SSGPHH1909 | 1.36 | 3/4 | 9 | 3/4 | 468 | 664 | 20 | 27 | 24 | 78 | 2.49 |
| 11.51SSGPHH1606 | 1.59 | 5/8 | 6 | 5/8 | 356 | 479 | 16 | 23 | 21 | 67 | 1.4 |
| 11.51SSGPHH1612 | 1.59 | 5/8 | 12 | 5/8 | 507 | 784 | 16 | 23 | 21 | 66 | 1.79 |
| 11.51SSGPHH1609 | 1.59 | 5/8 | 9 | 5/8 | 431 | 632 | 20 | 24 | 21 | 66 | 1.96 |
| 11.51SSGPHH2518 | 2.27 | 1 | 18 | 1 | 778 | 1,191 | 26 | 35 | 31 | 106 | 6.5 |
| 11.51SSGPHH2524 | 2.27 | 1 | 24 | 1 | 928 | 1,495 | 26 | 35 | 31 | 105 | 8.13 |
| 11.51SSGPHH1906 | 2.36 | 3/4 | 6 | 3/4 | 393 | 511 | 22 | 27 | 24 | 78 | 2.04 |
| 11.51SSGPHH1912 | 2.36 | 3/4 | 12 | 3/4 | 544 | 816 | 22 | 27 | 24 | 78 | 3.27 |
| 11.51SSGPHH2506 | 4.54 | 1 | 6 | 1 | 479 | 586 | 26 | 35 | 31 | 109 | 4.23 |
| 11.51SSGPHH2512 | 4.54 | 1 | 12 | 1 | 625 | 886 | 26 | 35 | 31 | 106 | 6.64 |

Blueprint

