



Turnbuckles Eye - Hook G-6314, Green Pin®

Product information

The Green Pin® EH Turnbuckle is a turnbuckle with eye-hook end-fittings. One of the unique features of Green Pin® Turnbuckles such as this one is that they can be used for both lifting and lashing. Galvanization of the Green Pin® EE Turnbuckle ensures its long-term durability. The turnbuckle is available in a range with a diameter thread 3/8" (take up of 6") up to 1" (take up of 24").

- **Standard:** generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b
- **Certification:** a works certificate, proof load test certificate and/or EC Declaration of Conformity can be supplied upon request.

Material: drop forged high tensile steel SAE 1035 or 1045

Marking: CE-marked

Temperature range: -20°C up to +200°C

Finish: hot dipped galvanized

Safety factor: 5:1

Part Code	WLL ton	Thread	Take up inch	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	Weight kg
11.51SSGPHO1006	0.54	3/8	6	285	422	13	16	15	10	13	29	49	0.47
11.51SSGPHO1212	0.68	1/2	12	466	750	13	19	16	12	18	36	57	1.28
11.51SSGPHO1206	1	1/2	6	315	445	16	22	16	12	18	36	58	0.82
11.51SSGPHO1209	1	1/2	9	390	598	16	22	16	12	18	36	57	1.06
11.51SSGPHO1606	1.02	5/8	6	368	491	16	23	21	14	21	45	79	1.31
11.51SSGPHO1612	1.02	5/8	12	519	796	16	23	21	14	21	45	78	1.71
11.51SSGPHO1909	1.36	3/4	9	479	675	20	27	24	17	26	54	89	4.49
11.51SSGPHO1609	1.59	5/8	9	443	644	20	24	21	14	21	45	78	1.56
11.51SSGPHO1906	2.27	1	6	488	595	26	35	31	24	36	75	118	3.87
11.51SSGPHO1918	2.27	1	18	789	1,202	26	35	31	24	36	75	117	6
11.51SSGPHO2512	2.27	1	24	939	1,506	26	35	31	24	36	75	116	7.52
11.51SSGPHO2506	2.36	3/4	6	403	521	22	27	24	17	26	54	89	2.04
11.51SSGPHO2518	2.36	3/4	12	554	827	22	27	24	17	26	54	88	2.3
11.51SSGPHO2524	2.36	3/4	18	707	1,133	22	27	24	17	26	54	89	2.85
11.51SSGPHO1912	4.54	1	12	636	897	26	35	31	24	36	75	117	5.09

Blueprint

