



Closed Body Rigging Screws G-6345

Product information

Closed body rigging screw with eye-jaw.

Material: mild steel

Marking: CE-marked

Finish: hot dipped galvanized

Note: end fittings of 6 and 8 mm rigging screws are electro-galvanized

Safety factor: 5:1

| Part Code | WLL ton | a mm | b mm | c mm | d mm | e mm | f mm | g mm | h mm | i mm | j mm | k mm | Weight kg |
|-----------------|------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--------------|
| - | 0.2 | 6 | 100 | 165 | 247 | 5 | 16 | 7 | 20 | 13 | 11 | 11 | 0.14 |
| - | 0.32 | 8 | 108 | 187 | 267 | 6 | 22 | 9 | 24 | 14 | 12 | 12 | 0.24 |
| - | 0.5 | 10 | 125 | 214 | 306 | 8 | 22 | 10.5 | 28 | 19 | 13 | 13 | 0.53 |
| - | 0.7 | 12 | 195 | 317 | 475 | 10 | 27 | 13 | 34 | 23 | 30 | 15 | 0.83 |
| - | 1.2 | 16 | 230 | 384 | 562 | 12 | 33 | 18 | 42 | 29 | 40 | 20 | 1.49 |
| 11.50SSGHGO200 | 1.5 | 20 | 270 | 452 | 657 | 16 | 38 | 20 | 51 | 33 | 50 | 24 | 2.54 |
| 11.50SSGHGO2200 | 2.2 | 22 | 295 | 493 | 717 | 20 | 45 | 25 | 55 | 38 | 50 | 24 | 3.34 |
| 11.50SSGHGO2400 | 3.2 | 24 | 325 | 539 | 791 | 22 | 52 | 30 | 70 | 46 | 56 | 28 | 4.65 |
| - | 4.8 | 33 | 370 | 670 | 952 | 30 | 70 | 38 | 82 | 60 | 70 | 35 | 10.5 |
| - | 6 | 39 | 400 | 714 | 1,011 | 33 | 70 | 45 | 85 | 76 | 80 | 40 | 12.8 |
| - | 8.5 | 45 | 400 | 741 | 945 | 39 | 86 | 50 | 94 | 85 | 49 | 49 | 20.8 |
| - | 11 | 48 | 400 | 774 | 1,018 | 45 | 97 | 58 | 98 | 92 | 52 | 52 | 24 |

Blueprint

