



DIN580 Eye Bolts C15

Product information

- **Standard:** generally to DIN 580
- **Certification:** at no extra charges this product can be supplied with a works certificate and/or EC Declaration of Conformity. Test certificates can be supplied upon request

Material: carbon steel, C15

Marking: CE-marked

Finish: self coloured or electro-galvanized

Safety factor: 6:1

Part Code	WLL ton	Thread mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	Weight kg/100pc
-	0.07	M6x1.00	M6x1.00	20	36	20	13	6	36	5.1
11.449199608	0.14	M8x1.25	M8x1.25	20	36	20	13	6	36	5.5
11.449199610	0.23	M10x1.5	M10x1.5	25	45	25	17	8	45	10.3
11.449199612	0.34	M12x1.75	M12x1.75	30	54	30	20.5	10	53	16.9
-	0.49	M14x2.00	M14x2.00	35	63	35	27	12	60	29.9
11.449199616	0.7	M16x2.00	M16x2.00	35	63	35	27	12	62	30.7
-	0.9	M18x2.50	M18x2.50	40	72	40	30	14	71	42.8
11.449199620	1.2	M20x2.5	M20x2.5	40	72	40	30	14	71	42.4

-	1.5	M22x2.5	M22x2.5	45	81	45	35	14	80	62.8
11.449199624	1.8	M24x3.00	M24x3.00	50	90	50	36	18	90	90.8
-	2.5	M27x3.00	M27x3.00	50	90	50	36	18	90	88.3
-	3.2	M30x3.50	M30x3.50	65	108	60	45	22	109	159
-	4.3	M33x3.50	M33x3.50	65	108	60	45	22	110	167
-	4.6	M36x4.00	M36x4.00	75	126	70	54	26	128	235
-	6.1	M39x4.00	M39x4.00	75	126	70	54	26	130	266
-	6.3	M42x4.50	M42x4.50	85	144	80	63	30	147	403
-	8	M45x4.50	M45x4.50	85	144	80	63	35	150	521
-	8.6	M48x5.00	M48x5.00	100	166	90	68	35	168	632
-	11.5	M56x5.50	M56x5.50	110	184	100	78	38	187	879
-	16	M64x6.00	M64x6.00	120	206	110	90	42	208	1,240
-	21	M72x6.00	M72x6.00	150	260	140	100	50	260	2,293
-	28	M80x6.00	M80x6.00	170	296	160	112	55	298	3,200
-	40	M100x6.00	M100x6.00	190	330	180	130	60	330	4,800

Blueprint

