



Double Swivel Hook DSH

Product information

The DSH hook-type lifting ring is a double swivel ring equipped with an automatic-locking eye hook. It consists of a steel ring that has a rotating range of 360°.

- Combine ring and hook into one piece
- Quick hanging
- Compatible with any kind of strand
- Available with latch hook

Marking: According to standard, CE-marked

Temperature range: -20°C up to + 200°C

Standard: EN 1677-1

except grade/WLL

Safety factor: 5:1

Grade: 8

| Part Code | WLL ton | Thread | Torque Nm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | L1 mm | S1 mm | S2 mm | X mm | Weight kg |
|---------------|---------|-------------|-----------|------|------|------|------|------|------|------|------|-------|-------|-------|------|-----------|
| 11.20DSH M 8 | 0.4 | M8 (x1,25) | 6 | 33 | 56 | 30 | 44 | 32 | 23 | 58 | 9.5 | 15 | 8 | 16 | 18 | 0.8 |
| 11.20DSH M 10 | 0.7 | M10 (x1,50) | 10 | 33 | 56 | 30 | 44 | 32 | 23 | 58 | 9.5 | 18 | 8 | 16 | 18 | 0.8 |
| 11.20DSH M 12 | 1.05 | M12 (x1,75) | 15 | 33 | 56 | 30 | 44 | 32 | 23 | 58 | 9.5 | 21 | 8 | 16 | 18 | 0.8 |
| 11.20DSH M 14 | 1.4 | M14 (x2) | 30 | 45 | 81 | 45 | 65 | 46 | 29 | 79 | 13 | 23 | 8 | 20 | 24 | 1.9 |
| 11.20DSH M 16 | 2 | M16 (x2) | 50 | 45 | 81 | 45 | 65 | 46 | 29 | 79 | 13 | 27 | 8 | 20 | 24 | 2 |
| 11.20DSH M 18 | 2.3 | M18 (x2,5) | 70 | 45 | 81 | 45 | 65 | 46 | 29 | 79 | 13 | 27 | 8 | 20 | 24 | 2 |
| 11.20DSH M 20 | 2.5 | M20 (x2,5) | 100 | 45 | 81 | 45 | 65 | 46 | 29 | 79 | 13 | 30 | 8 | 20 | 24 | 2 |

Technical data



Blueprint

