

Double swivel lifting point Codipro DSP



Product information

The DSP double swivel lifting point provides the option of adapting other lifting accessories: passing a cable or rope through it, placement of a ring with a large eye for using hooks that are disproportionate to the lifting ring,...

With its double swivel action, the DSP ring can be perfectly aligned with the sling. It consists of a steel ring that has a rotating range of 360°.

Features:

- 360° rotation.
- Swiveling under load.
- 180° articulation.
- Control anti-crack on 100% of the product.
- Fatigue test.

Marking: According to standard, CE-marked

Temperature range: -20°C up to + 200°C

Standard: EN 1677-1

Safety factor: 5:1

Part Code	WLL ton	Thread mm	Torque Nm	Standard mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	L1 mm	S1 mm	S2 mm	Weight kg
11.49DSP M 8	0.4	M 8 (x1.25)	6	15	33	56	30	19	19	58	9.5	15	8	16	0.3
11.49DSP M 10	0.7	M 10 (x1.50)	10	18	33	56	30	19	19	58	9.5	18	8	16	0.3
11.49DSP M 12	1.05	M 12 (x1.75)	15	21	33	56	30	19	19	58	9.5	21	8	16	0.3
11.49DSP M 14	1.4	M 14 (x2)	30	23	45	81	45	25	27	79	13	23	8	20	0.9
11.49DSP M 16	2	M 16 (x2)	50	27	45	81	45	25	27	79	13	27	8	20	0.9
11.49DSP M 18	2.3	M 18 (x2.5)	70	27	45	81	45	25	27	79	13	27	8	20	1
11.49DSP M 20	2.5	M 20 (x2.5)	100	30	45	81	45	25	27	79	13	30	8	20	1

Blueprint

