

## Basic-Lift AERO

### Product information



moving limits

The BASIC-LIFT is an all-rounder complementing the tried and tested AERO-LIFT® range of vacuum lifters. Without battery or inconvenient power cables and thus purely mechanical, it is absolutely independent. But yet this type can lift loads of 1.200 kg and above. Its safety is additionally guaranteed by vacuum gauge and a battery-operated warning device and meets the requirements of the EU norm EN 13155.

Handling is extremely easy. Every time the lifter is put down it automatically switches from „Suction“ to „Release“ and vice versa.



Part code	Code	WLL ton	Min. load kg	Plate Ø mm	Main beam length mm	Cross beam width mm	Weight kg
16.6068-1100400	BL 100 / 1L	0.1	2	1 / 230	-	-	15
16.6068-1100401	BL 400 / 1L	0.4	2	1 / 410	-	-	55
16.6068-1100402	BL 400 / 4L	0.4	3	4 / 280	2.2	1	100
16.6068-1100403	BL 600 / 2L	0.6	3	2 / 410	2.2	-	90
16.6068-1100601	BL 600 / 4L	0.6	3	4 / 340	2.2	1	115
16.6068-1100404	BL 600 / 3L	0.6	3	3 / 410	2.2	-	140
16.6068-1100602	BL 600 / 6L	0.6	3	6 / 280	2.2	1	140
16.6068-1100603	BL 600 / 8L	0.6	3	8 / 280	4	1	200
16.6068-1100750	BL 750 / 6L	0.75	3	6 / 340	4	1	160
16.6068-1100901	BL 900 / 6L	0.9	3	6 / 280	2.2	1	135
16.6068-1101201	BL 1200 / 4L	1.2	5	4 / 410	2.2	1	195
16.6068-1101202	BL 1200 / 6L	1.2	5	6 / 410	2.2	1	220
16.6068-1101203	BL 1200 / 8L	1.2	5	8 / 340	3	1	230