

DYNICE Dux Rope

Product information



High performance ropes for various applications with high strength and durability. These ropes combine good strength retention with good flexibility and dynamic properties. Making terminations is easy through splicing where up to 90% of linear strength is retained.

Design:

Very firm, heat set and stretched 12-strand Dyneema® SK99 rope with smooth Durapur impregnation for abrasion resistance. The constructional elongation has been removed in the production process and stretch is extremely low. Very popular for their roundness and smooth surface.

The ropes are soft and flexible and easy to splice.

Material: Dyneema®

Part Code	Diameter mm	MBL ton	MBL unspliced ton	Weight in sea kg	Weight kg
12.122913030	6	6.1	6.8	-0.26	3.28
12.122913047	8	8.9	9.9	-0.39	4.92
12.122913057	10	12.2	13.5	-0.55	6.8
12.122913068	12	16.9	18.8	-0.78	9.7
12.122913075	14	24.6	27.3	-1.09	13.6
12.122913090	16	33.5	37.2	-1.49	18.6
12.122913100	18	40.6	45.1	-1.81	22.6
12.122913110	20	49.2	54.7	-2.2	27.4

12.122913120	21	57.8	64.2	-2.57	32.1
12.122913130	23	66.2	73.6	-2.97	37
12.122913140	25	74.4	82.7	-3.38	42.1
12.122913150	27	81.5	90.6	-3.75	46.8
12.122913160	29	89	98.9	-4.15	51.7
12.122913170	31	96.4	107.1	-4.55	56.7
12.122913180	32	103.8	115.3	-4.95	61.7
12.122913190	33	111.8	124.2	-5.39	67.2
12.122913200	35	120.8	134.2	-5.88	73.3
12.122913210	37	131.5	146.1	-6.48	80.8
12.122913220	39	141	156.7	-7.03	87.7
12.122913230	41	151.7	168.5	-7.65	95.4
12.122913240	43	164.6	182.9	-8.4	104.7
12.122913250	45	177.8	197.5	-9.18	114.4
12.122913260	47	191.1	212.3	-9.99	124.5
12.122913270	49	204.7	227.4	-10.82	134.9
12.122913280	51	218.3	242.6	-11.68	145.6