



Wire Rope Lifting Sling WLS-000

Product information

Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²*

(*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm²)

Design: Endless, mechanically pressed with 2 alu. ferrules

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope constructions possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

Note: We recommend that the sling not is bent over a diameter less than 6 times the wire rope diameter without reducing the WLL.

| Part Code | WLL ton |
|-----------|---------|
| WLS00003 | 0.23 |
| WLS00004 | 0.42 |
| WLS00005 | 0.65 |
| WLS00006 | 0.94 |
| WLS00008 | 1.64 |
| WLS00009 | 2.07 |
| WLS00010 | 2.56 |
| WLS00011 | 3.1 |

| | |
|----------|-------|
| WLS00012 | 3.67 |
| WLS00013 | 4.33 |
| WLS00014 | 5.03 |
| WLS00016 | 6.57 |
| WLS00018 | 8.3 |
| WLS00020 | 10.24 |
| WLS00022 | 12.41 |
| WLS00028 | 16.8 |
| WLS00026 | 17.33 |
| WLS00024 | 17.46 |
| WLS00032 | 20.08 |
| WLS00036 | 26.25 |
| WLS00040 | 33.19 |
| WLS00044 | 41.11 |
| WLS00048 | 49.56 |
| WLS00052 | 59.1 |

Technical data