



## Snatch Block H - Hook

### Product information

Intended for general lifting purposes. Can also be used for pulling. WLL in table applies for load on head fitting/hook.

**Design:** Snatch block type with covering side plates. Provided with swiveling hook with latch. Bronze bushed sheave in 2-4 tons blocks and roller bearings in larger sizes. Grease fitting in the shaft and cross head.

**Material:** Steel.

**Marking:** Type, WLL and wire rope diameter.

**Finish:** Blue painted.

Part Code	Rope Ø range mm	WLL ton	TA mm	TB mm	TC mm	Ø D1 mm	Ø D2 mm	Weight kg
16.15121030214	7-9	2	82	70	290	75	58	4
16.15121040414	10-12	4	120	70	358	115	90	6
16.15121060414	16-19	4	160	70	432	150	120	14
16.15121080814	19-22	8	210	93	549	200	165	16
16.15121101014	24-26	10	260	115	695	250	205	38
16.15121121214	24-26	12	310	133	797	300	250	56
16.15121081514	22-24	15	210	102	672	200	165	24
16.15121121514	24-26	15	310	133	797	300	250	65
16.15121142214	28-32	22	365	140	960	355	305	90
16.15121123014	28-30	30	310	193	993	300	250	125
16.15121163014	32-35	30	415	155	1,121	405	350	135
16.15121143514	32-35	35	365	193	1,028	350	280	130
16.15121245014	46-50	50	625	275	1,495	600	500	418

## Blueprint

