

GL100 Cablegrip closed with thimble

Product information

General: Tool for mounting of wire ropes.

Design: Closed with one thimble.

Also available in special editions in larger sizes and stainless material.

Material: Galvanized steelwire 1960N/mm²



| Part Code | Rope Ø range mm | Length mm | Max. pullingforce kN | Thimble Ø mm |
|-------------------|--------------------|--------------|-------------------------|-----------------|
| 10.15KBZ106/1000 | 6-8 | 1,000 | 3.3 | 13 |
| 10.15KBZ108/1000 | 8-10 | 1,000 | 4.6 | 14 |
| 10.15KBZ110/1250 | 8-15 | 1,250 | 6.2 | 18 |
| 10.15KBZ115/1250 | 15-20 | 1,250 | 12.8 | 18 |
| 10.15KBZ120/1250 | 20-30 | 1,250 | 16 | 18 |
| 10.15KBZ130/1250 | 30-40 | 1,250 | 19.2 | 20 |
| 10.15KBZ140/1250 | 40-50 | 1,250 | 22.4 | 20 |
| 10.15KBZ150/1250 | 50-60 | 1,250 | 37.4 | 24 |
| 10.15KBZ160/1250 | 60-70 | 1,250 | 49.9 | 28 |
| 10.15KBZ170/1250 | 70-80 | 1,250 | 49.9 | 28 |
| 10.15KBZ180/1250 | 80-90 | 1,250 | 56.2 | 28 |
| 10.15KBZ190/1250 | 90-100 | 1,250 | 62.4 | 28 |
| 10.15KBZ1100/1250 | 100-115 | 1,250 | 62.4 | 28 |
| 10.15KBZ1115/1500 | 115-130 | 1,500 | 74.8 | 45 |
| 10.15KBZ1130/1500 | 130-150 | 1,500 | 74.8 | 45 |
| 10.15KBZ1150/1500 | 150-180 | 1,500 | 87.3 | 45 |
| 10.15KBZ1180/1500 | 180-210 | 2,000 | 99.8 | 60 |
| 10.15KBZ1210/1500 | 210-240 | 1,500 | 99.8 | 60 |

Technical data