



Coil Hook Type CKP

Product information



Unbalanced

General: For small to medium loads and thin coils. Often used after the splitting of wider coils. For further information, see the introductory text above in the section on C-hooks.

Design: Cut steel plate. The fork covers the entire coil width, and has a nose on the tip for additional safety. When unloaded, the hook hangs with the tip of the fork pointing upwards, which facilitates loading of the coil.

Proof: 1,5 x WLL.

Material: Plate of high-strength structural steel.

Marking: Type, working load limit, maximum coil width and CE marking.

Finish: Yellow painted.

Safety factor: 1,5 x WLL.

Part Code	Code	WLL ton	Max coil width mm	E mm	G mm	H mm	L mm	S mm	T mm	U mm	Weight kg
16.80CKP025060	CKP2,5-6	0.25	60	75	12	400	70	25	30	12	2
16.80CKP050120	CKP5-12	0.5	120	145	20	340	130	40	60	20	4.1
16.80CKP100205	CKP10-20,5	1	205	230	20	390	141	60	60	20	8.6
16.80CKP200265	CKP20-26,5	2	265	315	50	500	180	60	60	25	26
16.80CKP300280	CKP30-28	3	280	330	50	500	230	80	80	25	36
16.80CKP400450	CKP40-45	4	450	500	50	600	264	105	90	25	61

Blueprint

