

## Wall Jib Crane Underbraced 180° PMI

## Product information

The headroom is the main asset of the PMI. Its I beam profile allows to consider installation of a hoist with electric or manual steering. The PMT are delivered with standard mounting brackets and our mounting kits KITFIX (optional) ensure safe anchorages for specific supports.

A full range of accessories is available.

## Options

- Hoist power supply cable + lockable main switch
- Standpipe
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly
- Single or multipositions rotation lock
- Outdoor use
- Motorization
- Electric or manual hoist



Part code	WLL ton	Cap. kg	Span m 2,0	Span m 2,5	Span m 3,0	Span m 3,5	Span m 4,0	Span m 4,5	Span m 5,0	Span m 5,5	Span m 6,0	Span m 6,5	Span m 7,0
6025PMI015	0.15	150	•	•	٠	•	•	٠	•	•	•	•	•
6025PMI025	0.25	250	•	•	•	•	•	•	•	•	•	•	•
6025PMI050	0.5	500	•	•	•	•	•	•	•	•	•	•	•
6025PMI100	1	1,000	•	•	•	•	•	•	•	•	•	•	•
6025PMI160	1.6	1,600	•	•	•	•	•	•	•	•	•	-	-
6025PMI200	2	2,000	•	•	•	•	•	•	•	•	•	-	-
6025PMI250	2.5	2,500	•	•	•	•	•	•	•	-	-	-	-
6025PMI320	3.2	3,200	•	•	•	•	•	•	•	-	-	-	-
6025PMI400	4	4,000	•	•	•	•	•	•	•	-	-	-	-

## **Technical data**

Outreach (m) / Capacity (kg)	2	2,5	3	3,5	4	4,5	5	5,5	6	6,5
150	х	x	x	х	х	х	х	х	х	X
250	х	х	х	x	х	х	х	х	х	X
500	х	х	х	х	х	х	х	х	х	X
1000	х	x	х	x	х	x	х	х	х	X
1600	х	x	Х	х	х	х	х	х	х	
2000	х	x	x	x	х	х	х	х	х	
2500	х	x	Х	х	х	х	х			
3200	х	x	х	x	х	x	х			
4000	х	х	х	х	x	х	х			