

Wall Jib Crane Underbraced 180° PMI

Product information



The headroom is the main asset of the PMI. Its I beam profile allows to consider installation of a hoist with electric or manual steering. The PMI are delivered with standard mounting brackets and our mounting kits KITFIX (optional) ensure safe anchorages for specific supports.

A full range of accessories is available.

Options

- Hoist power supply cable + lockable main switch
- Standpipe
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly
- Single or multipositions rotation lock
- Outdoor use
- Motorization
- Electric or manual hoist

| Part Code | WLL ton | Cap. kg | Span m 2,0 | Span m 2,5 | Span m 3,0 | Span m 3,5 | Span m 4,0 | Span m 4,5 | Span m 5,0 | Span m 5,5 | Span m 6,0 | Span m 6,5 | Span m 7,0 |
|------------|---------|---------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| 6025PMI015 | 0.15 | 150 | • | • | • | • | • | • | • | • | • | • | • |
| 6025PMI025 | 0.25 | 250 | • | • | • | • | • | • | • | • | • | • | • |
| 6025PMI050 | 0.5 | 500 | • | • | • | • | • | • | • | • | • | • | • |
| 6025PMI100 | 1 | 1,000 | • | • | • | • | • | • | • | • | • | • | • |
| 6025PMI160 | 1.6 | 1,600 | • | • | • | • | • | • | • | • | • | - | - |
| 6025PMI200 | 2 | 2,000 | • | • | • | • | • | • | • | • | • | - | - |
| 6025PMI250 | 2.5 | 2,500 | • | • | • | • | • | • | • | - | - | - | - |
| 6025PMI320 | 3.2 | 3,200 | • | • | • | • | • | • | • | - | - | - | - |
| 6025PMI400 | 4 | 4,000 | • | • | • | • | • | • | • | - | - | - | - |

Technical data

| Outreach (m) / Capacity (kg) | 2 | 2,5 | 3 | 3,5 | 4 | 4,5 | 5 | 5,5 | 6 | 6,5 |
|---|----------|------------|----------|------------|----------|------------|----------|------------|----------|------------|
| 150 | x | x | x | x | x | x | x | x | x | x |
| 250 | x | x | x | x | x | x | x | x | x | x |
| 500 | x | x | x | x | x | x | x | x | x | x |
| 1000 | x | x | x | x | x | x | x | x | x | x |
| 1600 | x | x | x | x | x | x | x | x | x | |
| 2000 | x | x | x | x | x | x | x | x | x | |
| 2500 | x | x | x | x | x | x | x | | | |
| 3200 | x | x | x | x | x | x | x | | | |
| 4000 | x | x | x | x | x | x | x | | | |