



Pillar Jib Crane Overbraced 270° PFT

Product information

The PFT's beam is built on an I beam profile, appropriate for indoor or outdoor use. Its light weight gives it great flexibility for rotations of 270°. The structure of this jib crane is suitable for the optional installation of a hoist motor direction.

A full range of accessories is available.

Floor fixing is done with chemical anchors or anchor rods with foundation.

Options

- Installation template + anchor rods (or base plate for chemical anchors, keeping its limitations in mind).
- Hoist power supply cable.
- Lockable main switch.
- Rotation slowing device (adaptable without welding or mechanical intervention).
- Hot dip galvanizing (contact us).
- Rotation stops to weld onto the assembly, or adjustable.
- Single or multiposition's rotation lock.
- Electric or manual hoist.
- Outdoor use.

Cap. kg	Span m 2,0	Span m 2,5	Span m 3,0	Span m 3,5	Span m 4,0	Span m 4,5	Span m 5,0	Span m 5,5	Span m 6,0	Span m 6,5	Span m 7,0
150	•	•	•	•	•	•	•	•	٠	•	•
250	•	•	•	•	•	•	•	•	•	•	•
500	•	•	•	•	•	•	•	•	•	•	•
1,000	•	•	•	•	•	•	•	•	•	•	•
1,600	•	•	•	•	•	•	•	-	-	-	-
2,000	•	•	•	•	•	•	•	-	-	-	-

Technical data

Outreach (m) / Capacity (kg)	2	2,5	3	3,5	4	4,5	5	5,5	6	7
150	х	х	х	х	х	х	х	х	х	х
250	х	х	х	х	х	х	х	х	х	х
500	х	х	х	х	х	х	х	х	х	х
1000	х	х	х	х	х	x	х	х	х	х
1600	х	Х	х	х	х	х				
2000	х	х	х	х	х	х				