



## Snatch Block McKissick 419 with Shackle - Light Champion

## **Product information**

The McKissick snatch block 419 Light Champion from Crosby is a snatch block fitted with a shackle. Available from WLL 2 up to 15 T. Can be delivered with bronze bushing (BB) and from WLL 8 T also with roller bearing (RB).

## Features:

- Bolt for opening feature is retained, to ensure no lost bolts.
- Opening feature permits easy insertion of rope without reeving, or while the block is suspended.
- Center pin equipped with pressure lube fitting.
- All sizes feature sheave grooves suited for a range of wire line diameters.
- Meets or exceeds all requirements of ASME B30.26 including identification ductility, design factor, proof load and temperature requirements.
- Meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.

Material: Forged steel. Marking: CE-marked

Safety factor: 4:1

| Part code   | Code      | Rope Ø range<br>mm | WLL<br>ton | Sheave dia<br>mm | Bearing | A<br>mm | B<br>mm | C<br>mm | D<br>mm | E<br>mm | F<br>mm | G<br>mm | H<br>mm | Weight<br>kg |
|-------------|-----------|--------------------|------------|------------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--------------|
| 16.15109037 | 419 w/eye | 8-10               | 2          | 76               | BB      | 220     | 76      | 67      | 168     | 14      | 14      | 35      | 35      | 1.8          |
| 16.15109091 | 419       | 8-10               | 2          | 76               | BB      | 235     | 76      | 67      | 185     | 13      | 13      | 34      | 40      | 2.3          |
| 16.15109064 | 419       | 10-13              | 4          | 114              | BB      | 340     | 108     | 79      | 268     | 16      | 18      | 43      | 51      | 5.4          |
| 16.15109126 | 419       | 16-19              | 8          | 152              | BB      | 481     | 152     | 106     | 373     | 32      | 32      | 76      | 88      | 12.7         |
| 16.15109153 | 419       | 16-19              | 8          | 152              | RB      | 481     | 152     | 106     | 373     | 32      | 32      | 76      | 88      | 12.7         |
| 16.15109224 | 419       | 16-19              | 8          | 203              | BB      | 533     | 206     | 106     | 398     | 32      | 32      | 76      | 88      | 15           |
| 16.15109251 | 419       | 16-19              | 8          | 203              | RB      | 533     | 206     | 106     | 398     | 32      | 32      | 76      | 88      | 15           |
| 16.15109322 | 419       | 16-19              | 8          | 254              | BB      | 586     | 257     | 106     | 425     | 32      | 32      | 76      | 88      | 19.5         |
| 16.15109359 | 419       | 16-19              | 8          | 254              | RB      | 586     | 257     | 106     | 425     | 32      | 32      | 76      | 88      | 19.5         |
| 16.15202961 | 419       | 16-19              | 8          | 305              | BB      | 657     | 308     | 106     | 471     | 32      | 32      | 76      | 88      | 24.9         |
| 16.15109420 | 419       | 16-19              | 8          | 356              | BB      | 695     | 359     | 106     | 484     | 32      | 32      | 76      | 88      | 30.4         |
| 16.15109457 | 419       | 16-19              | 8          | 356              | RB      | 695     | 359     | 106     | 484     | 32      | 32      | 76      | 88      | 30.4         |

## Blueprint

