



Swivel Eye / Hook Crosby S6

Product information

Design: Swivel with eye and hook equipped with tapered roller thrust bearing.

Features:

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- All hooks furnished with latches
- Other types and capacities up to 1250 t available on demand.

Marking: CE-marked

Note: Always check before use if your steel wire rope is suitable for use with a swivel.

Warning: Not to be used on demolition- (wrecking-) balls!

Safety factor: 5:1

| Part Code | Diameter mm | WLL ton | Rope Ø mm | Swivel No | E mm | F mm | G mm | L mm | M mm | P mm | Q mm | R mm | S mm | T mm | V mm | Weight kg |
|-------------|-------------|---------|-----------|-----------|------|------|------|------|------|------|------|------|------|------|------|-----------|
| 11.46297066 | - | 3 | 13 | 3-S-6 | 292 | 123 | 70,0 | 38,9 | 35,8 | 36,6 | 19,1 | 26,2 | 28,4 | 31,8 | 28,4 | 4.23 |
| 11.46297262 | - | 5 | 16 | 5-S-6 | 332 | 160 | 76,0 | 49,3 | 42,9 | 46,0 | 25,4 | 32,5 | 31,8 | 31,8 | 36,6 | 6.46 |
| 11.46297468 | 0 | 8.5 | 19 | 8-S-6 | 408 | 192 | 102 | 62,5 | 56,5 | 57,0 | 31,8 | 35,8 | 41,1 | 38,1 | 41,1 | 14.5 |
| 11.46297663 | - | 10 | 22 | 10-S-6 | 486 | 212 | 114 | 66,0 | 61,0 | 66,0 | 42,9 | 42,9 | 70,0 | 47,8 | 49,3 | 20.6 |
| 11.46297869 | - | 15 | 26 | 15-S-6 | 540 | 263 | 127 | 71,5 | 61,0 | 76,0 | 49,3 | 51,5 | 70,0 | 54,0 | 60,5 | 28.6 |
| 11.46298163 | - | 25 | - | 25-S-6 | 699 | 346 | 152 | 87,5 | 92,0 | 93,0 | 57,0 | 58,5 | 98,5 | 60,5 | 76,0 | 61 |
| 11.46298261 | - | 35 | - | 35-S-6 | 780 | 357 | 165 | 98,5 | 95,5 | 116 | 57,0 | 58,5 | 98,5 | 60,5 | 81,0 | 98 |
| 11.46298369 | - | 45 | - | 45-S-6 | 907 | 392 | 178 | 121 | 108 | 129 | 63,5 | 64,5 | 102 | 76,0 | 82,5 | 122 |

Blueprint

