



VARI Pump S D- 230V - 1 Stage

Product information

Holmatro VARI Basic Pump units. To control your hydraulic system, Holmatro offers a various range of basic pump units.

Complement the basic pump unit with hydraulic components such as pressure gauges and control valves, making it possible to assemble the complete pump unit to meet your specific or future needs.

- 230V, 400V or petrol driven
- 1 or 2 stage

Unique specifications:

- In case of a power failure, the oil pressure is maintained
- Protected against pressure drop by pressure-controlled non-return valve
- Excluding single-acting (M311) or double-acting (M322 or M323) control valve
- TIP: If you want to create flexibility for future single acting or double acting use; add a Sada switch (M304) to your pump set-up

Features: Safe; in case of a power failure, the oil pressure is maintained.

Code	max. working pressure bar/Mpa	oil capacity cc	Engine	L mm	W mm	H mm	Weight kg
06 S 06 D	720 / 72	6,000	230 VAC-1.1 kW-50 Hz-1 PH	400	300	411	36
12 S 06 D	720 / 72	6,000	230 VAC-1.5 kW-50 Hz-1 PH	400	300	441	38
06 S 12 D	720 / 72	12,000	230 VAC-1.1 kW-50 Hz-1 PH	400	300	541	44
12 S 12 D	720 / 72	12,000	230 VAC-1.5 kW-50 Hz-1 PH	400	3,200	541	46