



Chain Sling CSX-175 Grade 10

Product information

Design: Chain sling with master link on one end and clevis load hook on the other end. \varnothing 26 mm chain is fitted with an eye hook. Other combinations possible on demand.

Dimensions: \varnothing 6–26 mm (other dimensions on demand).

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Part Code	WLL ton
11.91CSX17506XXX	1.4
11.91CSX17506005	1.4
11.91CSX17506010	1.4
11.91CSX17506015	1.4
11.91CSX17506020	1.4
11.91CSX17506030	1.4
11.91CSX17506040	1.4

11.91CSX17506050	1.4
11.91CSX17506060	1.4
11.91CSX17507XXX	1.9
11.91CSX17507005	1.9
11.91CSX17507010	1.9
11.91CSX17507015	1.9
11.91CSX17507020	1.9
11.91CSX17507030	1.9
11.91CSX17507040	1.9
11.91CSX17507050	1.9
11.91CSX17507060	1.9
11.91CSX17508XXX	2.5
11.91CSX17508005	2.5
11.91CSX17508010	2.5
11.91CSX17508015	2.5
11.91CSX17508020	2.5
11.91CSX17508030	2.5
11.91CSX17508040	2.5
11.91CSX17508050	2.5
11.91CSX17508060	2.5
11.91CSX17510XXX	4
11.91CSX17510005	4
11.91CSX17510010	4

11.91CSX17510015	4
11.91CSX17510020	4
11.91CSX17510030	4
11.91CSX17510040	4
11.91CSX17510050	4
11.91CSX17510060	4
11.91CSX17513XXX	6.7
11.91CSX17513005	6.7
11.91CSX17513010	6.7
11.91CSX17513015	6.7
11.91CSX17513020	6.7
11.91CSX17513030	6.7
11.91CSX17513040	6.7
11.91CSX17513050	6.7
11.91CSX17513060	6.7
11.91CSX17516XXX	10
11.91CSX17516005	10
11.91CSX17516010	10
11.91CSX17516015	10
11.91CSX17516020	10
11.91CSX17516030	10
11.91CSX17516040	10
11.91CSX17516050	10

11.91CSX17516060	10
11.91CSX17519XXX	14
11.91CSX17519005	14
11.91CSX17519010	14
11.91CSX17519015	14
11.91CSX17519020	14
11.91CSX17519030	14
11.91CSX17519040	14
11.91CSX17519050	14
11.91CSX17519060	14
11.91CSX17522XXX	19
11.91CSX17522005	19
11.91CSX17522010	19
11.91CSX17522015	19
11.91CSX17522020	19
11.91CSX17522030	19
11.91CSX17522040	19
11.91CSX17522060	19
11.91CSX17526XXX	26.5
11.91CSX17526005	26.5
11.91CSX17526010	26.5
11.91CSX17526015	26.5
11.91CSX17526020	26.5

11.91CSX17526030

26.5

11.91CSX17526040

26.5

11.91CSX17526050

26.5

11.91CSX17526060

26.5