



Chain Sling CSX-176 Grade 10

Product information

Design: Chain sling with master link on one end and clevis safety hook on the other end.
 ø 19 and 22 mm chain are fitted with an eye safety hook. Other combinations possible on demand.

Dimensions: Ø 6–22 mm (other dimensions on demand).

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Part Code	WLL ton
11.91CSX17606XXX	1.4
11.91CSX17606005	1.4
11.91CSX17606010	1.4
11.91CSX17606015	1.4
11.91CSX17606020	1.4
11.91CSX17606030	1.4
11.91CSX17606040	1.4
11.91CSX17606050	1.4

11.91CSX17606060	1.4
11.91CSX17607XXX	1.9
11.91CSX17607005	1.9
11.91CSX17607010	1.9
11.91CSX17607015	1.9
11.91CSX17607020	1.9
11.91CSX17607030	1.9
11.91CSX17607040	1.9
11.91CSX17607050	1.9
11.91CSX17607060	1.9
11.91CSX17608XXX	2.5
11.91CSX17608005	2.5
11.91CSX17608010	2.5
11.91CSX17608015	2.5
11.91CSX17608020	2.5
11.91CSX17608030	2.5
11.91CSX17608040	2.5
11.91CSX17608050	2.5
11.91CSX17608060	2.5
11.91CSX17610XXX	4
11.91CSX17610005	4
11.91CSX17610010	4
11.91CSX17610015	4

11.91CSX17610020	4
11.91CSX17610030	4
11.91CSX17610040	4
11.91CSX17610050	4
11.91CSX17610060	4
11.91CSX17613XXX	6.7
11.91CSX17613005	6.7
11.91CSX17613010	6.7
11.91CSX17613015	6.7
11.91CSX17613020	6.7
11.91CSX17613030	6.7
11.91CSX17613040	6.7
11.91CSX17613050	6.7
11.91CSX17613060	6.7
11.91CSX17616XXX	10
11.91CSX17616005	10
11.91CSX17616010	10
11.91CSX17616015	10
11.91CSX17616020	10
11.91CSX17616030	10
11.91CSX17616040	10
11.91CSX17616050	10
11.91CSX17616060	10

11.91CSX17619XXX	14
11.91CSX17619005	14
11.91CSX17619010	14
11.91CSX17619015	14
11.91CSX17619020	14
11.91CSX17619030	14
11.91CSX17619040	14
11.91CSX17619050	14
11.91CSX17619060	14
11.91CSX17622XXX	19
11.91CSX17622005	19
11.91CSX17622010	19
11.91CSX17622015	19
11.91CSX17622020	19
11.91CSX17622030	19
11.91CSX17622040	19
11.91CSX17622050	19
11.91CSX17622060	19