



Chain Sling CSX-476 Grade 10

Product information

Design: Chain sling with master link on one end and clevis safety hook on the other end of each leg. \varnothing 19 and 22 mm chain are fitted with eye safety hooks. Other combinations possible on demand.

Dimensions: \varnothing 6–22 mm (other dimensions on demand).

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Part Code	WLL ton
11.91CSX47606005	3
11.91CSX47606010	3
11.91CSX47606015	3
11.91CSX47606020	3
11.91CSX47606030	3
11.91CSX47606040	3
11.91CSX47606050	3
11.91CSX47606060	3

11.91CSX47606XXX	3
11.91CSX47607005	4
11.91CSX47607010	4
11.91CSX47607015	4
11.91CSX47607020	4
11.91CSX47607030	4
11.91CSX47607040	4
11.91CSX47607050	4
11.91CSX47607060	4
11.91CSX47607XXX	4
11.91CSX47608005	5.3
11.91CSX47608010	5.3
11.91CSX47608015	5.3
11.91CSX47608020	5.3
11.91CSX47608030	5.3
11.91CSX47608040	5.3
11.91CSX47608050	5.3
11.91CSX47608060	5.3
11.91CSX47608XXX	5.3
11.91CSX47610005	8
11.91CSX47610010	8
11.91CSX47610015	8
11.91CSX47610020	8

11.91CSX47610030	8
11.91CSX47610040	8
11.91CSX47610050	8
11.91CSX47610060	8
11.91CSX47610XXX	8
11.91CSX47613005	14
11.91CSX47613010	14
11.91CSX47613015	14
11.91CSX47613020	14
11.91CSX47613030	14
11.91CSX47613040	14
11.91CSX47613050	14
11.91CSX47613060	14
11.91CSX47613XXX	14
11.91CSX47616005	21.2
11.91CSX47616010	21.2
11.91CSX47616015	21.2
11.91CSX47616020	21.2
11.91CSX47616030	21.2
11.91CSX47616040	21.2
11.91CSX47616050	21.2
11.91CSX47616060	21.2
11.91CSX47616XXX	21.2

11.91CSX47619005	30
11.91CSX47619010	30
11.91CSX47619015	30
11.91CSX47619020	30
11.91CSX47619030	30
11.91CSX47619040	30
11.91CSX47619050	30
11.91CSX47619060	30
11.91CSX47619XXX	30
11.91CSX47622005	40
11.91CSX47622010	40
11.91CSX47622015	40
11.91CSX47622020	40
11.91CSX47622030	40
11.91CSX47622040	40
11.91CSX47622050	40
11.91CSX47622060	40
11.91CSX47622XXX	40