

## Rope Pear Socket Nemag



### Product information

The Nemag Rope Pear Socket is designed to, in combination with the Nemag Quick Release Link, smoothly pass over cable sheaves. The life span of the Nemag Rope Pear Socket generally surpasses that of the steel wire rope. The Rope Pear socket can be fitted by casting with a 2-component casting mass without the need for outside assistance, and ensures a strong connection. Nemag Rope Pear Sockets are suited to any type of steel wire rope.

**Material:** High grade casted steel.

**Marking:** Manufacturers logo, size and batch number.

**Warning:** The specified capacities shown are for grab operation. For other applications use safety factor 5:1

**Safety factor:** 5:1

Part Code	Code	Rope Ø range mm	WLL ton	MBL	Weight kg
10.10NRPS01	RP-1	10-11	1.5	10	0.4
10.10NRPS02	RP-2	12-13	2	14	0.4
10.10NRPS03	RP-3	14-15	2.5	17.5	0.6
10.10NRPS04	RP-4	16-17	3	22.5	0.9
10.10NRPS05	RP-5	18-19	4.5	27.5	1.3
10.10NRPS06	RP-6	20-21	5	35	1.5
10.10NRPS07	RP-7	22-24	7	42.5	2.2
10.10NRPS08	RP-8	25-27	8	52.5	2.4
10.10NRPS09	RP-9	28-30	11	70	3.7
10.10NRPS10	RP-10	31-33	13	85	4.1
10.10NRPS11	RP-11	34-36	15	95	5.9
10.10NRPS12	RP-12	37-39	17	110	6.7
10.10NRPS13	RP-13	40-42	21	125	9.3
10.10NRPS14	RP-14	43-45	26	155	10.5
10.10NRPS15	RP-15	46-48	30	180	12.1
10.10NRPS17	RP-17	52-56	42.5	240	21.3

## Technical data

### Combination of the Nomag Rope Pear Socket with Nomag Quick Release Link

A Rope Pear Socket can be fitted to a Quick Release Link of the same size, or to a link with a different size as indicated in table

<b>Pear code:</b>	<b>Link code:</b>
RP-2	
RP-3	RL-4
RP-4	RL-4 / RL-5
RP-5	RL-4 / RL-5 / RL-6
RP-6	RL-5 / RL-6 / RL-7
RP-7	RL-6 / RL-7 / RL-8 / RL-9
RP-8	RL-7 / RL-8 / RL-9
RP-9	RL-8 / RL-9 / RL-10
RP-10	RL-9 / RL-10 / RL-11
RP-11	RL-10 / RL-11 / RL-12
RP-12	RL-11 / RL-12 / RL-13
RP-13	RL-12 / RL-13 / RL-14
RP-14	RL-13 / RL-14 / RL-15
RP-15	RL-14 / RL-15
RP-17	RL-17

# Blueprint

