



## Eye Sling Hook Pewag HSWP

### Product information

This eye sling hook is ideally suited for the pewag winner pro Connex system. It is universally usable and comes with a forged and galvanised safety catch that locks into the tip of the hook, thereby providing excellent protection against lateral shifts. The safety catch with a latch, the safety pin and the stainless spring are available as a spare parts set for each hook and easy and quick to replace by a competent person.

**Material:** Alloy steel.

**Marking:** According to standard, CE-marked, Pewag or PW, winner pro or 12, H16, batch code and type.

**Temperature range:** -60°C up to +300°C.

**Finish:** Light blue powdercoated.

**Standard:** EN 1677-2

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 12

| Part Code  | Code     | WLL<br>ton | LC<br>kN | EWL | a<br>mm | b<br>mm | d1<br>mm | d2<br>mm | e<br>mm | g1<br>mm | h<br>mm | Weight<br>kg |
|------------|----------|------------|----------|-----|---------|---------|----------|----------|---------|----------|---------|--------------|
| 11.1288001 | HSWP 7/8 | 3          | 60       | 106 | 19      | 88      | 25       | 11       | 106     | 26       | 27      | 0.65         |
| 11.1288003 | HSWP 10  | 5          | 100      | 131 | 26      | 108     | 34       | 16       | 131     | 31       | 33      | 1.29         |
| 11.1288005 | HSWP 13  | 8          | 160      | 164 | 33      | 132     | 43       | 19       | 164     | 39       | 43      | 2.43         |

# Blueprint

