



Master Link Pewag MW Enlarged

Product information

MW Enlarged master links are designed for the assembly of chain slings. Can also be attached to wire rope slings. For pewag connex and welded system.

Master link SAW: Without flattened part for transition link and special colour.

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Part Code	Code	WLL ton	EWL	Use for hook DIN 15401 Nr	For chain Ø 1-leg MW I mm	For chain Ø 2-leg MW II mm	Double hook DIN 15402 no.	d mm	s mm	t mm	w mm	Weight kg
11.0261990	MW 10	1.4	90	2,5	5	5	4	11	10	90	65	0.22
11.0261993	MW 13	2.3	120	4	6+7	6	5	14	10	120	70	0.44
11.0261996	MW 16	3.2	140	5	8	7	6	16	13	140	80	0.71
11.0262001	MW 18	4.2	160	6	10	8	8	18	14	160	95	1.09
11.0298533	MW 22	6.7	170	10	13	10	12	23	17	170	105	1.74
11.0262008	MW 26	10.1	190	10	16	13	12	27	20	190	110	2.65
11.0262011	MW 32	16	230	12	19	16	16	33	26	230	130	4.78
11.0262014	MW 36	21.2	275	20	22	19	25	38	29	275	150	7.48
11.0270801	MW 56	40	350	50	32	26	63	56	46	350	250	21.98

Blueprint

