



Master Link Assembly Pewag VMW Enlarged

Product information

VMW Enlarged master link assemblies are designed for pewag connex and welded system. For assembling 3- and 4-leg chains with connex links CW. For assembling of welded chain slings with BW by pewag. Similar to VW 4-leg set, but also suitable for larger crane hooks and special hooks.

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

| Part Code | Code | WLL ton | EWL | Consisting of | Use for hook DIN 15401 Nr | Double hook DIN 15402 no. | e mm | t mm | w mm | Weight kg |
|------------|-----------|---------|-----|-----------------|---------------------------|---------------------------|------|------|------|-----------|
| 11.0262075 | VMW 6 | 4.2 | 214 | MW 18 + 2 BW 13 | 6 | 8 | 214 | 160 | 95 | 1.43 |
| 11.0262076 | VMW 7/8 | 6.6 | 240 | MW 22 + 2 BW 16 | 10 | 12 | 240 | 170 | 105 | 2.46 |
| 11.0262078 | VMW 10 | 10.1 | 275 | MW 26 + 2 BW 20 | 10 | 12 | 275 | 190 | 110 | 4.01 |
| 11.0262080 | VMW 13 | 15.7 | 345 | MW 32 + 2 BW 22 | 12 | 16 | 345 | 230 | 130 | 7.1 |
| 11.0262082 | VMW 16 | 21.2 | 415 | MW 36 + 2 BW 26 | 20 | 25 | 415 | 275 | 150 | 11.3 |
| 11.0244238 | VMW 19/20 | 34.1 | 500 | MW 56 + 2 BW 32 | 50 | 63 | 500 | 350 | 250 | 28.3 |
| 11.0270814 | VMW 22 | 40 | 520 | MW 56 + 2 BW 36 | 50 | 63 | 520 | 350 | 250 | 30.22 |

Blueprint

