



## Special Master Link Assembly Pewag VAW

### Product information

VAW For pewag connex and welded system. For assembling 3- and 4-leg chains with connex links CW, when shortening hooks are to be assembled separately, and for slings with thimble eyes.

For use in rope slings please consider that load capacity is listed according to EN 1677-4 with safety factor 4.

For assembling of welded slings with BW by pewag.

**Material:** High duty grade 10

**Marking:** According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type

**Temperature range:** -40°C up to +380°C

**Finish:** Orange powder coated

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

Part Code	Code	WLL ton	EWL	Consisting of	Use for hook DIN15401 Nr	Double hook DIN 15402 no.	e mm	t mm	w mm	Weight kg
11.0231892	VAW 6/7	5	245	AW 18 + 2 AW 14	5	6	245	135	75	1.72
11.0231940	VAW 8	6.3	270	AW 22 + 2 AW 16	6	8	270	160	90	2.66
11.0231941	VAW 10	9.5	315	AW 26 + 2 AW 18	8	10	315	180	100	4.3
11.0231950	VAW 13	16.1	380	AW 32 + 2 AW 26	10	12	380	200	110	9.06
11.0231955	VAW 16	25.1	460	AW 36 + 2 AW 32	16	20	460	260	140	14.53
11.0231973	VAW 19/20	41.1	625	AW 50 + 2 MW 36	32	40	625	350	190	31.51
11.0231992	VAW 22	47.4	690	AW 50 + 2 AW 45	32	40	690	350	190	42.19
11.0271790	VAW 26	58	750	AW 56 + 2 AW 50	32	40	750	400	200	56.4
11.0254806	VAW 32	85	860	AW 72 + 2 AW 56	50	63	860	460	250	99.02

## Blueprint

