



Oversize Clevis Master Set Pewag LXKW 1

Product information

This oversized clevis master set is frequently used on mobile cranes. It consists of an LW master ring and a welded-in XKW shortening hook for the creation of I-leg chain slings in the assembled system. The chain is mounted directly into the captive coupling of the shortening element, thereby eliminating the need for an additional connecting link. Assembly and disassembly of the system by a competent person is easy and quick, without the need for special tools.

The hook functions both as a connecting link and a shortening element and the master link is suitable for crane hooks up to no. 25 according to DIN 15401 and up to no. 32 according to DIN 15402.

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.

Standard: EN 818-4

Safety factor: 4:1

Grade: 10

Part Code	Code	WLL ton	EWL	Use for hook DIN 15401 no.	Double hook DIN 15402 no.	d mm	e mm	t mm	w mm	Weight kg
11.0287885	LXKW 1-6	1.4	478	25	32	23	478	340	180	3.72
11.0287886	LXKW 1-8	2.5	516	25	32	23	516	340	180	4.03
11.0287887	LXKW 1-10	4	569	25	32	27	569	340	180	6.05
11.0287888	LXKW 1-13	6.7	629	25	32	27	629	340	180	8.82
11.0287889	LXKW 1-16	10	688	25	32	33	688	340	180	13.54

Blueprint

