



Master Link Assembly Pewag VSAW 2

Product information

VSAW is designed for assembling of welded chain slings with transition links BW by pewag. For assembling of chain slings with Connex CW.

The flattened section on the rings make them universally adaptable and the extra-large interior dimensions of the rings make them easy to use with single hooks according to DIN 15401 no. 50/100 or double hooks according to DIN 15402 no. 63/125.

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

| Part Code | Code | WLL ton | EWL | Consisting of | Double hook DIN 15402 no. | Can be used up to single hook acc. to DIN 15401 no. | d | e | t | w | Weight kg |
|------------|--------------------|------------|-----|----------------|---------------------------|---|----|-----|-----|-----|--------------|
| | | | | | | | mm | mm | mm | mm | |
| 11.0298031 | VSAW 2-10/13/4-10 | 9.5 | 585 | SAW 32+2 BW 20 | 63 | 50 | 33 | 585 | 500 | 250 | 10.68 |
| 11.0298033 | VSAW 2-16/4-13 | 14 | 575 | SAW 40+2 BW 22 | 63 | 50 | 40 | 575 | 460 | 250 | 15.44 |
| 11.0298035 | VSAW 2-19/20/4-16 | 21.2 | 640 | SAW 45+2 BW 26 | 63 | 50 | 45 | 640 | 500 | 250 | 21.64 |
| 11.0298037 | VSAW 2-22/4-19/20 | 30 | 610 | SAW 50+2 BW 32 | 63 | 50 | 50 | 610 | 460 | 250 | 27.3 |
| 11.0298039 | VSAW 2-26/4-22 | 40 | 610 | SAW 56+2 BW 32 | 63 | 50 | 56 | 610 | 460 | 250 | 34.92 |
| 11.0298041 | VSAW 2-26/4-22/320 | 40 | 950 | SAW 60+2 BW 32 | 125 | 100 | 60 | 950 | 800 | 320 | 56.24 |

Blueprint

