



Connex Connecting Link Pewag CW

Product information

CW Connex connecting link for pewag connex system.

Load pin and collar CBH are also separately available.

Connecting link for:

Master link - chain, chain - chain, hook - chain.

Only for straight pull.

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.

Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

| Part Code | Code | WLL ton | LC kN | EWL | b mm | c mm | d mm | e mm | g mm | s mm | t mm | Weight kg |
|------------|----------|------------|----------|-----|---------|---------|---------|---------|---------|---------|---------|--------------|
| 11.064757 | CW 5 | 1 | 20 | 38 | 34 | 7 | 7 | 38 | 13 | 9 | 12 | 0.06 |
| 11.064457 | CW 6 | 1.4 | 28 | 44 | 39 | 8 | 8 | 44 | 14 | 11 | 13 | 0.08 |
| 11.062823 | CW 7 | 1.9 | 36 | 53 | 46 | 10 | 9 | 53 | 17 | 13 | 16 | 0.14 |
| 11.0689347 | CW 8 | 2.5 | 50 | 62 | 55 | 12 | 10 | 62 | 19 | 14 | 20 | 0.24 |
| 11.0689340 | CW 10 | 4 | 80 | 72 | 64 | 15 | 13 | 72 | 24 | 18 | 22 | 0.42 |
| 11.062693 | CW 13 | 6.7 | 134 | 88 | 79 | 20 | 17 | 88 | 28 | 22 | 26 | 0.85 |
| 11.0690112 | CW 16 | 10 | 200 | 112 | 105 | 24 | 24 | 112 | 34 | 29 | 35 | 1.9 |
| 11.0690085 | CW 19/20 | 16 | 320 | 126 | 123 | 32 | 25 | 126 | 42 | 35 | 45 | 3.1 |
| 11.0690041 | CW 22 | 19 | 380 | 157 | 148 | 36 | 26 | 157 | 51 | 39 | 46 | 4.6 |
| 11.0689021 | CW 26 | 26.5 | 530 | 190 | 175 | 40 | 30 | 190 | 60 | 46 | 49 | 6.8 |
| 11.0689023 | CW 32 | 40 | 800 | 206 | 216 | 47 | 35 | 206 | 80 | 56 | 63 | 11.2 |

Blueprint

