



## Clevis Safety Hook Pewag KLHW

### Product information

KLHW Clevis safety hooks are designed for the assembly of chain slings.  
Closes and locks automatically.

**Material:** High duty grade 10.

**Marking:** According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

**Temperature range:** -40°C up to +380°C.

**Finish:** Orange powder coated.

**Standard:** EN 1677-3

**Safety factor:** 4:1

**Grade:** 10

Part code	Code	WLL ton	EWL	a mm	b mm	d mm	e mm	g mm	h mm	s max. mm	Weight kg
11.1632024	KLHW 5/6	1.4	94	17	71	7.4	94	28	20	1	0.56
11.1632047	KLHW 7	1.9	123	20	88	9	123	34	26	1	0.87
11.1632011	KLHW 8	2.5	123	20	88	10	123	34	26	1	1
11.1632052	KLHW 10	4	144	29	107	12.5	144	45	30	1	1.61
11.1632054	KLHW 13	6.7	180	35	138	16	180	52	40	1.5	3.25
11.1632056	KLHW 16	10	218	41	168	20	218	60	50	2	5.95
11.1684653	KLHW 19/20	16	259	50	194	24	259	70	62	2	12.89
11.1684657	KLHW 22	19	286	52	211	27	286	81	65	2	15.91
11.1684740	KLHW 26	26.5	338	61	253	33	338	100	79	2	21.33

## Blueprint

