



Eye Sling Hook Pewag HSW

Product information

HSW Eye sling hooks are designed for the assembly of chain slings. All hooks with forged safety catch. For general lifting applications.

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.

Standard: EN 1677-2

Safety factor: 4:1

Grade: 10

Part code	Code	WLL ton	LC kN	EWL	a mm	b mm	d1 mm	d2 mm	e mm	g1 mm	h mm	Weight
11.1167237	HSW 5/6	1.4	28	85	17	68	20	10	85	19	21	0.3
11.1167239	HSW 7/8	2.5	50	106	19	88	25	11	106	26	27	0.5
11.1167241	HSW 10	4	80	131	26	109	34	16	131	31	33	1.1
11.1167243	HSW 13	6.7	134	164	33	134	43	19	164	39	44	2.2
11.1167245	HSW 16	10	200	183	40	155	50	25	183	45	50	3.5
11.1167247	HSW 19/20	16	320	205	48	178	55	27	205	53	55	5.8
11.1167187	HSW 22	19	380	225	50	196	60	29	225	62	62	8
11.1170516	HSW 26	26.5	530	259	70	235	70	37	259	73	75	13.4
11.1188728	HSW 32	40	800	299	82	291	66	45	299	87	97	27.5

Blueprint

