



Foundry Hook Pewag FW

Product information

Hook for applications where jaw size "g" of the HSW hook is inadequate, mainly foundries.
Before using the hook, check whether hooks without safety latch are allowed to be used for this particular application.

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.

Standard: EN 1677-1

Note: Can't be mounted with Unilock U!

Safety factor: 4:1

Grade: 10

Part Code	Code	WLL ton	EWL	a mm	b mm	d1 mm	d2 mm	e mm	g mm	h mm	Weight kg
11.1454866	FW 7/8	2.5	131	25	118	24	11	131	64	29	0.94
11.1454867	FW 10	4	158	32	143	31	14	158	76	35	1.62
11.1454868	FW 13	6.7	190	40	170	39	17	190	89	42	3.24
11.1454869	FW 16	10	224	46	200	47	22	224	102	50	5.65
11.1454870	FW 19/20	16	260	54	231	56	28	260	114	61	9.5
11.1003410	FW 22	19	265	63	264	47	31	287	140	75	13.4
11.1003413	FW 26	26.5	305	73	312	82	38	358	152	84	21.4
11.1003415	FW 32	40	327	90	359	66	44	370	170	101	34

Blueprint

