

HXW/HSXW horizontal lifting clamps



Product information

General: For horizontal lifting and moving of steel plates. Clamp with compact shape and relative light unit weight. HXW/HSXW pewag winner lifting clamps **must always be used in pairs (or multiples thereof)**. Lifting capacity and jaw opening are clearly engraved in the body. The Working Load Limits indicated are per pair of lifting clamps. The HSXW clamps have a larger jaw opening.

Note: The given WLL is valid per pair.

| Part Code | Code | WLL ton | Jaw width mm | H mm | S mm | T mm | U mm | V mm | W mm | X mm | Y mm | Weight kg |
|-------------|----------|---------|--------------|------|------|------|------|------|------|------|------|-----------|
| 16.01HXW1t | HXW 1 t | 1 | 0-35 | 11.5 | 99 | 25 | 188 | 140 | 10 | 65 | 15 | 2.6 |
| 16.01HXW2t | HXW 2 t | 2 | 0-60 | 19.5 | 118 | 30.5 | 287 | 180 | 15 | 90 | 16 | 7 |
| 16.01HXW3t | HXW 3 t | 3 | 0-60 | 19.5 | 118 | 30.5 | 291 | 180 | 20 | 90 | 16 | 8 |
| 16.01HXW4t | HXW 4 t | 4 | 0-60 | 19.5 | 145 | 30.5 | 304 | 220 | 25 | 105 | 20 | 13 |
| 16.01HXW6t | HXW 6 t | 6 | 0-60 | 19.5 | 145 | 30.5 | 307 | 220 | 25 | 110 | 20 | 14 |
| 16.01HXW8t | HXW 8 t | 8 | 0-60 | 19.5 | 135 | 30.5 | 336 | 225 | 35 | 120 | 30 | 19 |
| 16.01HXW10t | HXW 10 t | 10 | 0-60 | 19.5 | 135 | 30.5 | 336 | 225 | 35 | 120 | 30 | 19 |
| 16.01HXW12t | HXW 12 t | 12 | 0-60 | 19.5 | 135 | 30.5 | 336 | 225 | 35 | 120 | 30 | 19 |
| 16.01HXW15t | HXW 15 t | 15 | 0-60 | 21.5 | 147 | 43 | 344 | 262 | 35 | 160 | 35 | 30 |
| 16.01HXW25t | HXW 25 t | 25 | 0-60 | 21.5 | 147 | 43 | 349 | 262 | 40 | 175 | 35 | 33 |

Blueprint

