

## HXW/HSXW horizontal lifting clamps



### Product information

**General:** For horizontal lifting and moving of steel plates. Clamp with compact shape and relative light unit weight. HXW/HSXW pewag winner lifting clamps **must always be used in pairs (or multiples thereof)**. Lifting capacity and jaw opening are clearly engraved in the body. The Working Load Limits indicated are per pair of lifting clamps. The HSXW clamps have a larger jaw opening.

**Note:** The given WLL is valid per pair.

| Part Code   | Code     | WLL ton | Jaw width mm | H mm | S mm | T mm | U mm | V mm | W mm | X mm | Y mm | Weight kg |
|-------------|----------|---------|--------------|------|------|------|------|------|------|------|------|-----------|
| 16.01HXW1t  | HXW 1 t  | 1       | 0-35         | 11.5 | 99   | 25   | 188  | 140  | 10   | 65   | 15   | 2.6       |
| 16.01HXW2t  | HXW 2 t  | 2       | 0-60         | 19.5 | 118  | 30.5 | 287  | 180  | 15   | 90   | 16   | 7         |
| 16.01HXW3t  | HXW 3 t  | 3       | 0-60         | 19.5 | 118  | 30.5 | 291  | 180  | 20   | 90   | 16   | 8         |
| 16.01HXW4t  | HXW 4 t  | 4       | 0-60         | 19.5 | 145  | 30.5 | 304  | 220  | 25   | 105  | 20   | 13        |
| 16.01HXW6t  | HXW 6 t  | 6       | 0-60         | 19.5 | 145  | 30.5 | 307  | 220  | 25   | 110  | 20   | 14        |
| 16.01HXW8t  | HXW 8 t  | 8       | 0-60         | 19.5 | 135  | 30.5 | 336  | 225  | 35   | 120  | 30   | 19        |
| 16.01HXW10t | HXW 10 t | 10      | 0-60         | 19.5 | 135  | 30.5 | 336  | 225  | 35   | 120  | 30   | 19        |
| 16.01HXW12t | HXW 12 t | 12      | 0-60         | 19.5 | 135  | 30.5 | 336  | 225  | 35   | 120  | 30   | 19        |
| 16.01HXW15t | HXW 15 t | 15      | 0-60         | 21.5 | 147  | 43   | 344  | 262  | 35   | 160  | 35   | 30        |
| 16.01HXW25t | HXW 25 t | 25      | 0-60         | 21.5 | 147  | 43   | 349  | 262  | 40   | 175  | 35   | 33        |

# Blueprint

