



## Standard Reeve Crane Blocks 1 Sheave

### Product information

#### General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

#### Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

#### Important:

**Inquiries for custom versions are welcome!**

WLL ton	Model	For wire Ø mm	Hook size	Weight kg
12.5	SRB 225 .14 .1 .12,5 .E	14	5	75
12.5	SRB 260 .14 .1 .12,5 .E	14	5	110
12.5	SRB 260 .16 .1 .12,5 .E	16	5	110
16	SRB 225 .14 .1 .16 .E	14	5	100

16	SRB 260 .16 .1 .16 .E	16	5	110
16	SRB 285 .16 .1 .16 .E	16	6	160
16	SRB 320 .16 .1 .16 .E	16	6	160
16	SRB 320 .19 .1 .16 .E	19	6	160
16	SRB 355 .16 .1 .16 .E .A	16	6	180
16	SRB 355 .19 .1 .16 .E	19	6	180
20	SRB 355 .19 .1 .20 .E	19	10	225
29	SRB 400 .22 .1 .29 .E	22	8	290
32	SRB 450 .24 .1 .32 .E .A	24	10	455
32	SRB 450 .26 .1 .32 .E .A	26	10	455
32	SRB 450 .24 .1 .32 .E .B	24	10	590
32	SRB 450 .26 .1 .32 .E .B	26	10	590
40	SRB 450 .24 .1 .40 .E .B	24	12	590
40	SRB 450 .26 .1 .40 .E	26	12	590
50	SRB 528 .24 .1 .50 .E	24	16	725
50	SRB 528 .26 .1 .50 .E	26	16	725
50	SRB 528 .28 .1 .50 .E	28	16	725
50	SRB 575 .28 .1 .50 .E	28	16	930
63	SRB 630 .32 .1 .63 .E	32	16	1,000
63	SRB 670 .28 .1 .63 .E	28	16	1,800
63	SRB 670 .32 .1 .63 .E	32	16	1,800

# Blueprint

