



Standard Reeve Crane Blocks 3 Sheaves

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

WLL	Model	For wire Ø mm	Hooksize	Weight kg
25	SRB 260 .14 .3 .25 .E	14	8	210
25	SRB 260 .16 .3 .25 .E	16	8	210
29	SRB 285 .16 .3 .29 .E	16	8	210
29	SRB 320 .16 .3 .29 .E	16	8	225
32	SRB 355 .19 .3 .32 .E	19	10	325
40	SRB 360 .19 .3 .40 .E	19	12	455
40	SRB 400 .22 .3 .40 .E	22	12	500
50	SRB 400 .22 .3 .50 .E	22	16	500
50	SRB 400 .22 .3 .50 .E	22	16	540
63	SRB 450 .22 .3 .63 .E	22	16	680
63	SRB 450 .24 .3 .63 .E	24	16	770
63	SRB 450 .26 .3 .63 .E	26	16	770
80	SRB 528 .26 .3 .80 .E	24	20	1,270
80	SRB 528 .26 .3 .80 .E	26	20	1,270
100	SRB 528 .26 .3 .100 .E	26	25	1,270
100	SRB 528 .28 .3 .100 .E	28	25	1,270
125	SRB 670 .28 .3 .125 .E	28	25	2,900
125	SRB 670 .32 .3 .125 .E	32	25	2,900

Blueprint

