



Standard Reeve Crane Blocks 4 sheaves

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

WLL	Model	For wire Ø mm	Hooksize	Weight kg
35	SRB 285 .16 .4 .35 .E	16	10	260
50	SRB 355 .19 .4 .50 .E	19	16	475
63	SRB 400 .22 .4 .63 .E	22	16	525
63	SRB 450 .22 .4 .63 .E	22	16	725
80	SRB 450 .24 .4 .80 .E	24	20	960
80	SRB 450 .26 .4 .80 .E	26	20	960
100	SRB 528 .26 .4 .100 .E	26	25	1,250
100	SRB 528 .28 .4 .100 .E	28	25	1,250
160	SRB 670 .28 .4 .160 .E	28	40	3,150
160	SRB 670 .32 .4 .160 .E	32	40	3,150