



Fast Reeve Crane Blocks 1 sheave

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

WLL	Model	For wire Ø mm	Hooksize	Weight kg
12.5	FRB 225 .14 .1 .12,5 .E	14	4	90
12.5	FRB 260 .14 .1 .12,5 .E	14	4	100
12.5	FRB 260 .16 .1 .12,5 .E	16	4	100

16	FRB 225 .14 .1 .16 .E	14	6	100
16	FRB 260 .14 .1 .16 .E	14	6	120
16	FRB 260 .16 .1 .16 .E	16	6	120
16	FRB 285 .16 .1 .16 .E	16	6	135
16	FRB 355 .16 .1 .16 .E	16	6	180
16	FRB 355 .19 .1 .16 .E .A	19	6	180
16	FRB 355 .19 .1 .16 .E .B	19	6	225
20	FRB 260 .14 .1 .20 .E	14	8	130
20	FRB 260 .16 .1 .20 .E	16	8	130
20	FRB 285 .16 .1 .20 .E	16	8	160
20	FRB 320 .16 .1 .20 .E	16	8	160
20	FRB 355 .16 .1 .20 .E	16	8	250
20	FRB 355 .19 .1 .20 .E	19	8	250
25	FRB 400 .19 .1 .25 .E	19	8	275
25	FRB 400 .22 .1 .25 .E	22	8	275
29	FRB 400 .22 .1 .29 .E	22	8	365
32	FRB 450 .26 .1 .32 .E .A	26	10	450
32	FRB 450 .22 .1 .32 .E	22	10	455
32	FRB 450 .24 .1 .32 .E .A	24	10	455
32	FRB 450 .24 .1 .32 .E .B	24	10	590
32	FRB 450 .26 .1 .32 .E .B	26	10	590
40	FRB 450 .22 .1 .40 .E	22	12	590
40	FRB 450 .24 .1 .40 .E	24	12	590

40	FRB 450 .26 .1 .40 .E	26	12	590
40	FRB 528 .24 .1 .40 .E	24	12	680
40	FRB 528 .26 .1 .40 .E	26	12	680
40	FRB 528 .28 .1 .40 .E	28	12	680
40	FRB 575 .26 .1 .40 .E	26	12	750
50	FRB 450 .26 .1 .50 .E .A	26	16	590
50	FRB 450 .26 .1 .50 .E .B	26	16	680
50	FRB 528 .24 .1 .50 .E	24	16	750
50	FRB 528 .26 .1 .50 .E	26	16	750
50	FRB 528 .28 .1 .50 .E	28	16	750
50	FRB 575 .28 .1 .50 .E	28	16	750
50	FRB 630 .28 .1 .50 .E	28	16	975
63	FRB 575 .32 .1 .63 .E	32	16	975
63	FRB 630 .32 .1 .63 .E	32	16	975
63	FRB 670 .28 .1 .63 .E	28	16	1,800
63	FRB 670 .32 .1 .63 .E	32	16	1,800

Blueprint

