



Fast Reeve Crane Blocks 2 sheave

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

WLL	Model	For wire Ø mm	Hooksize	Weight kg
16	FRB 225 .14 .2 .16 .E	14	6	105
16	FRB 260 .14 .2 .16 .E	14	6	125
16	FRB 260 .16 .2 .16 .E	16	6	125

20	FRB 260 .14 .2 .20 .E	14	8	130
20	FRB 260 .16 .2 .20 .E	16	8	130
20	FRB 285 .16 .2 .20 .E	16	8	160
20	FRB 320 .16 .2 .20 .E	16	8	160
25	FRB 320 .16 .2 .25 .E	16	8	205
29	FRB 355 .19 .2 .29 .E	19	8	265
29	FRB 400 .19 .2 .29 .E	19	8	365
29	FRB 400 .22 .2 .29 .E	22	8	365
32	FRB 450 .22 .2 .32 .E	22	10	485
40	FRB 450 .22 .2 .40 .E	22	12	590
40	FRB 450 .24 .2 .40 .E	24	12	590
40	FRB 450 .26 .2 .40 .E	26	12	590
50	FRB 450 .24 .2 .50 .E	22	16	680
50	FRB 450 .26 .2 .50 .E	26	16	680
63	FRB 528 .24 .2 .63 .E	24	16	1,000
63	FRB 528 .26 .2 .63 .E	26	16	1,000
63	FRB 528 .28 .2 .63 .E	28	16	1,000
80	FRB 528 .26 .2 .80 .E	26	20	1,065
80	FRB 528 .28 .2 .80 .E	28	20	1,065
100	FRB 670 .28 .2 .100 .E	28	20	2,240
100	FRB 670 .32 .2 .100 .E	32	20	2,240

Blueprint

