



Fast Reeve Crane Blocks 4 sheave

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

WLL	Model	For wire Ø mm	Hooksize	Ø D1 mm	Ø D2 mm	B mm	O mm	TA mm	TB mm	TL mm	L mm	T mm	Ø Z mm	Weight kg
35	FRB 285 .16 .4 .35 .E	16	12	320	285	753	84	420	292	1,053	1,171	28	32	275
50	FRB 355 .19 .4 .50 .E	19	12	410	355	959	84	500	363	1,229	1,347	35	37	500
63	FRB 400 .22 .4 .63 .E	22	16	460	400	1,038	97	570	350	1,333	1,465	40	43	540
63	FRB 355 .19 .4 .63 .E	19	16	410	355	1,038	97	500	343	1,308	1,440	35	37	570
63	FRB 450 .22 .4 .63 .E	22	16	515	450	1,038	97	600	400	1,448	1,580	40	43	750
63	FRB 450 .24 .4 .63 .E	24	16	515	450	1,038	97	600	400	1,448	1,580	45	52	750
80	FRB 450 .24 .4 .80 .E	24	20	515	450	1,183	110	600	527	1,568	1,718	45	52	1,000
80	FRB 450 .26 .4 .80 .E	26	20	515	450	1,183	110	600	527	1,568	1,718	40	52	1,000
80	FRB 528 .24 .4 .80 .E	24	20	595	528	1,272	110	710	527	1,736	1,886	45	52	1,000
80	FRB 528 .26 .4 .80 .E	26	20	595	528	1,272	110	710	527	1,736	1,886	45	52	1,000
80	FRB 528 .28 .4 .80 .E	28	20	595	528	1,273	110	710	472	1,671	1,821	40	59	1,270
100	FRB 528 .26 .4 .100 .E	26	25	595	528	1,288	132	710	472	1,743	1,913	40	52	1,270
100	FRB 528 .28 .4 .100 .E	28	25	595	528	1,288	132	710	472	1,753	1,923	40	59	1,270
125	FRB 575 .28 .4 .125 .E	28	32	650	575	1,413	137	770	442	1,893	2,083	40	59	1,360
160	FRB 670 .28 .4 .160 .E	28	40	760	670	1,616	167	870	662	2,181	2,393	50	59	3,150
160	FRB 670 .32 .4 .160 .E	32	40	760	670	1,616	167	870	662	2,181	2,393	60	66	3,150

Blueprint

