



Fast Reeve Crane Blocks 6 sheave

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

WLL	Model	For wire Ø mm	Hooksize	B mm	L mm	O mm	T mm	TA mm	TB mm	TL mm	Ø D1 mm	Ø D2 mm	Ø Z mm	Weight kg
63	FRB 360 .19 .6 .63 .E .A	19	16	973	-	97	30	510	522	1,243	420	360	37	680
63	FRB 360 .19 .6 .63 .E .B	19	16	973	-	97	30	510	522	1,243	420	360	37	725
63	FRB 400 .19 .6 .63 .E	19	16	1,063	-	97	30	570	507	1,363	460	400	37	775
80	FRB 400 .19 .6 .80 .E	19	20	1,147	1,597	110	30	570	507	1,447	460	400	43	820
80	FRB 400 .22 .6 .80 .E	22	20	1,147	1,597	110	40	570	507	1,447	460	400	43	820
80	FRB 450 .22 .6 .80 .E	22	20	1,187	1,730	110	40	600	502	1,580	515	450	43	910
80	FRB 450 .24 .6 .80 .E	24	20	1,187	1,730	110	45	600	502	1,580	515	450	52	910
100	FRB 450 .24 .6 .100 .E	24	25	1,263	1,768	132	45	600	582	1,598	515	450	52	1,135
100	FRB 450 .26 .6 .100 .E	26	25	1,263	1,768	132	45	600	582	1,598	515	450	52	1,135
150	FRB 528 .24 .6 .150 .E	24	40	1,553	2,232	167	45	710	642	2,020	596	528	52	1,800
150	FRB 528 .26 .6 .150 .E	26	40	1,553	2,232	167	45	710	642	2,020	596	528	52	1,800
150	FRB 528 .28 .6 .150 .E	28	40	1,553	2,242	167	50	710	642	2,030	596	528	59	1,800
160	FRB 528 .26 .6 .160 .E	26	40	1,581	2,178	167	45	710	682	1,966	596	528	52	2,270
160	FRB 528 .28 .6 .160 .E	28	40	1,581	2,188	167	50	710	682	1,976	596	528	59	2,270
200	FRB 575 .28 .6 .200 .E	28	50	1,661	2,317	188	50	770	602	2,081	650	575	59	2,270
235	FRB 670 .28 .6 .235 .E	28	50	1,716	2,442	188	50	870	952	2,206	760	670	59	4,160
235	FRB 670 .32 .6 .235 .E	32	50	1,716	2,442	188	60	870	952	2,206	760	670	66	4,160

Blueprint

