

## Samson wire rope blocks 3 sheave



### Product information

**General:**

- Up to 30 ton blocks standard supplied with swivel oval eye.
- Over 30 ton blocks standard supplied with swivel stud eye.
- Blocks can be supplied with swivel hook, swivel stud eye or swivel jaw on request.
- Standard supplied with bronze bearings. Other bearings available on request.
- Groove in sheave may be adjusted to other wire rope diameters on request.
- Blocks can be supplied with becket on request.

**Temperature range:** -40°C / +80°C

**Note:** WLL= Working Load Limit on head fitting

**Safety factor:** 4:1

Part Code	WLL ton	For wire Ø mm	No of Sheav.	D1 mm	D2 mm	F mm	Ø G mm	Ø J mm	K mm	L mm	M mm	R mm	TA mm	TB mm	TL mm	Weight kg
16.13111250230	2	10	3	125	105	27	22	16	26	58	24	5,5	135	120	336	9
16.13111500430	4	12	3	150	120	40	30	26	40	94	33	6,5	170	166	468	17
16.13112000630	6	14	3	200	165	40	30	29	45	108	42	7,5	220	166	556	28
16.13112500830	8	18	3	250	210	45	35	32	49	114	45	9,5	270	185	633	46
16.13113001030	10	20	3	300	255	50	40	36	54	125	52	11	320	204	733	69
16.13113501230	12	22	3	350	305	50	45	41	60	144	56	12	380	212	823	99
16.13113501630	16	24	3	350	305	60	50	46	66	163	64	13	380	258	880	120
16.13114001630	16	24	3	400	345	60	50	46	66	163	64	13	430	250	927	157
16.13113502030	20	24	3	350	305	60	50	51	72	173	72	13	380	258	896	143
16.13114002030	20	24	3	400	345	60	60	51	72	173	72	13	430	266	1,006	184
16.13113502530	25	24	3	350	305	60	50	60	80	195	76	13	380	266	955	170
16.13114002530	25	24	3	400	345	60	60	60	80	195	76	13	430	266	1,065	198
16.13114502530	25	28	3	450	390	70	70	60	80	195	76	15	480	296	1,120	220
16.13114003030	30	28	3	400	345	60	60	60	90	220	80	15	430	266	1,095	215
16.13114503030	30	28	3	450	390	70	70	60	90	220	80	15	480	296	1,140	255
16.13114004030	40	28	3	400	345	60	60	-	96	96	90	15	430	278	945	250
16.13114504030	40	28	3	450	390	70	70	-	96	96	90	15	480	308	1,030	295
16.13114505030	50	28	3	450	390	70	75	-	106	106	100	15	480	338	1,055	335

# Blueprint

